

Chattahoochee Trailer
Phone: 7062230699
5100 Veterans Pkwy
Columbus, GA
Email: tina@chattahoocheetrailer.com



2024 Hawke Trailers 7X12TA 12K Low Profile Dump Trailer

| | | |
|--|-------------------------|-----------------------|
| Stock#: HH-000591 | VIN#: 7PWFL1229RM000591 | Year: 2024 |
| Manufacturer: Hawke Trailers | Width: 80" or 6'8" | Length: 144" or 12'0" |
| Height: 24" or 2'0" | Weight: 3400 | GVWR: 12000 |
| Payload: 8600 | Color: BLACK | #Axles: 2 |
| Axle Capacity: 6000.00 | | |
| URL: https://chattahoocheetrailer.com/2024-hawke-trailers-7x12ta-12k-low-profile-dump-trailer-IUjp.html | | |

| | |
|-------|------------|
| Price | \$9,995.00 |
|-------|------------|

Description

- 7 X 12 TANDEM AXLE LOW PROFILE DUMP TRAILER
- TARP INSTALLED
- BATTERY CHARGER
- RAMPS
- SPARE MOUNT
- 2 WAY REAR GATE
- 2 FT SIDES
- SCISSOR LIFT

Our premium features **Hawke Low Profile Dump Trailers** are offered in 7,000, 10,000, 12,000, and 14,000 lb. GVWR's -- as well as a heavy duty 15,000 GVWR version. Scissor lift is standard as are slide-in loading ramps. The sides are 24" tall with two-way tailgates that open for unobstructed dumping or can be set in spreader mode for spreading gravel. An adjustable coupler is included as standard. The 7,000 and 10,000 GVWR models have a 6" channel main frame. The 12,000 and 14,000 GVWR models are built with a rugged 8" channel main frame. Cylinder sizes are matched to the model capacity. The 7,000 through 14,000 GVWR models employ the standard duty scissor lift. The 15,000 GVWR heavy duty version adds a super duty scissor lift with 5" cylinder and G range radial tires. The tongue upgrades to 8" channel and floor crossmembers are 12" on center making this trailer suitable for heavy duty commercial applications. These changes are highlighted in bold type on the specs page. Dexter brand axles along with premium Westlake radial tires on all models provide a long life running gear.

GVWR : 12,000 lb.
Capacity : 8,400 lb.
SPECIFICATIONS

- Two 6,000 lb. Dexter Brand Braking Axles
- Double Eye Spring Suspension
- 235/80 R16 Load Range E10 Ply Rating Westlake Radial Tires
- 8" Channel Main Frame -- 6" Channel Tongue
- 3x3 Tubing Dump Box Frame With 3" Channel Crossmembers
- 12 Gauge Floor
- 80" Inside Box With 24" Sides And No Stick Bottom Corners
- US Made Pump With Deep Cycle Battery Inside Lockable Security Box With 20' Hand Remote
- Two Way Tailgate Opens For Dumping Bulk Materials Or Can Be Set In Spreader Mode
- 80" 3" Channel Slide-In Loading Ramps
- 2 5/16" Adjustable Coupler
- 7,000 lb. Drop Foot Jack
- Safety Chains And Break-a-Way Switch
- LED Lighting With Reflective Tape
- Primed with epoxy primer and two coats of polyurethane paint
-